

2008 PermaGreen™ Magnum Specifications

engine 6.5 hp Honda GX200-RH2
overhead valves
horizontal drive shaft
hour meter / tachometer with maintenance timer

clutch Honda built-in wet clutch one-half reduction gearbox

transmission Peerless transaxle with reverse, neutral and 2 forward production gears

speed 5mph (high gear)-3,000 ft² / minute
3.5mph (low gear)-2,000 ft² / minute

fuel tank 0.95 gal. custom-design

spreader 150+ lb. PermaGreen hopper
LESCO type mechanism and rate adjustment
mechanically driven spinner
remote-operated LESCO deflector
remote-operated 3rd-hole adjuster
shower cap & stainless steel screen included

sprayer tank: 12.0 gal.
coverage: 50,000 ft² @ 30 oz. / 1,000 ft²
pump: 2 gpm diaphragm, mechanically driven
width of spray: 11.0 ft. broadcast, 3.0 ft. trim
broadcast nozzles: (2) Spraying Systems Turbo FloodJet for maximum drift reduction
trim nozzles: (2) Hypro Ultra low drift
one nozzle set (broadcast & trim) for high gear & low gear
manually operated valves for selection of nozzle type

frame 100% heavy-gauge, laser cut & precision stamped 300 series stainless steel

tires front- 9.50-8 x 18 Knobby tread
rear- 6.50-6 x 12 Turf type tread

brakes 4.0" band brakes on the sulky
mechanically operated by a foot peddle

dimensions 55" (l) x 35.5" (w) x 41" (h) [with handle down]

weight empty: 440.0 lb.
full: 690 lb. + driver