

2009 PermaGreen™ SmartSteer Specifications

engine 200cc Honda™ GX200-RH2
overhead valves, horizontal drive shaft
raised up from frame for easy cleaning
hour meter / tachometer with maintenance timer

clutch Honda™ built-in wet clutch one-half reduction gearbox

transmission Peerless™ 855 transaxle with reverse, natural and 2 forward production gears

speed 5mph (high gear)-3,000 ft² / minute
3.5mph (low gear)-2,000 ft² / minute

fuel tank 0.95 gal. custom-design

spreader 150+ lb. PermaGreen™ hopper
3-hole type mechanism or your choice of spreader, plus rate adjustment
mechanically driven spinner
remote-operated deflector
remote-operated pattern adjuster
shower cap & stainless steel screen included

sprayer tank: 12.0 gal.
coverage: 50,000 ft² @ 30 oz. / 1,000 ft²
pump: 2 gpm diaphragm, mechanically driven
width of spray: 11.0 ft. broadcast, 3.0 ft. trim
broadcast nozzles: (2) Spraying Systems Turbo FloodJe™t for maximum drift reduction
trim nozzles: (2) Hypro™ Ultra low drift
one nozzle set (broadcast & trim) for high gear & low gear
manually operated valves for selection of nozzle type

frame **100%** heavy-gauge, laser cut & precision stamped 300 series stainless steel

sulky articulated joints, cushioned foot pads

tires front- 9.50-8 x 18" Cushioning tread
rear- 6.50-6 x 13" Turf type tread

brakes 4.0" band brakes on the sulky
mechanically operated by a foot peddle

dimensions .55" (l) x 35.5" (w) x 41" (h) [with handle down]

weight empty: 440.0 lb
full: 690 lb. + driver